The listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1. (Previously amended) An apparatus for induction heating, said apparatus comprising:

a plurality of heat transfer plates, each of said heat transfer plates being disposed radially with respect to a magnetic core axis; and

a plurality of magnetic core sections disposed between respective pairs of said heat transfer plates and shaped to form a cylindrical magnetic core assembly.

- 2. (Previously amended) The apparatus of claim 1 wherein said cylindrical magnetic core assembly has the shape of a circular cylinder.
- (Previously amended) The apparatus of claim 1 further comprising a cylindrical outer shell disposed to surround said cylindrical magnetic core assembly.
- 4. (Original) The apparatus of claim 3 wherein said cylindrical outer shell comprises a metal or combination of metals.
- (Original) The apparatus of claim 3 wherein said cylindrical outer shell comprises a material or combination of materials selected from the group consisting of aluminum nitride and boron nitride.
- 6. (Original) The apparatus of claim 1 wherein said heat transfer plates comprise a metal or combination of metals.
- 7. (Original) The apparatus of claim 1 wherein said heat transfer plates comprise a material or combination of materials selected from the group consisting of aluminum nitride and boron nitride.

- 8. (Previously amended) The apparatus of claim 1 wherein said magnetic core sections comprise a ferromagnetic material.
- 9. (Withdrawn) The apparatus of claim 1 further comprising a coil winding disposed above said cylindrical core assembly.
- 10. (Withdrawn) The apparatus of claim 1 further comprising an annular coil winding disposed at least partially inside an annular recess in said cylindrical core assembly.
- 11. (Withdrawn) The apparatus of claim 1 further comprising a support platform disposed above said cylindrical core assembly.
- 12. (Withdrawn) The apparatus of claim 1 further comprising a heat sink disposed below and thermally coupled to said cylindrical core assembly.
  - 13. (Withdrawn) An apparatus for induction heating, said apparatus comprising:
- a plurality of heat transfer plates, each of said heat transfer plates being disposed radially with respect to a core axis;
- a plurality of core sections disposed between respective pairs of said heat transfer plates and shaped to form a cylindrical core assembly;
  - a support platform disposed above said cylindrical core assembly; and
- a heat sink disposed below and thermally coupled to said cylindrical core assembly.
- 14. (Withdrawn) The apparatus of claim 13 wherein said cylindrical core assembly has the shape of a circular cylinder.
- 15. (Withdrawn) The apparatus of claim 13 further comprising a cylindrical outer shell disposed to surround said cylindrical core assembly.

- 16. (Withdrawn) The apparatus of claim 13 wherein said heat transfer plates comprise a metal or combination of metals.
- 17. (Withdrawn) The apparatus of claim 13 wherein said core sections comprise a ferromagnetic material.
- 18. (Withdrawn) The apparatus of claim 13 further comprising a coil winding disposed above said cylindrical core assembly.
- 19. (Withdrawn) The apparatus of claim 13 further comprising an annular coil winding disposed at least partially inside an annular recess in said cylindrical core assembly.
- 20. (Previously amended) A method of making an apparatus for induction heating, said method comprising:

disposing a plurality of heat transfer plates radially with respect to a magnetic core axis; and

disposing a plurality of magnetic core sections between respective pairs of said heat transfer plates, said magnetic core sections being shaped to form a cylindrical magnetic core assembly.

- 21. (Previously amended) The method of claim 20 wherein said cylindrical magnetic core assembly has the shape of a circular cylinder.
- 22. (Previously amended) The method of claim 20 further comprising disposing a cylindrical outer shell to surround said cylindrical magnetic core assembly.
- 23. (Original) The method of claim 20 wherein said heat transfer plates comprise a metal or combination of metals.
- 24. (Original) The method of claim 20 wherein said heat transfer plates comprise a material or combination of materials selected from the group consisting of aluminum nitride and boron nitride.

- 25. (Previously amended) The method of claim 20 wherein said magnetic core sections comprise a ferromagnetic material.
- 26. (Withdrawn) The method of claim 20 further comprising disposing a coil winding above said cylindrical core assembly.
- 27. (Withdrawn) The method of claim 20 further comprising disposing an annular coil winding at least partially inside an annular recess in said cylindrical core assembly.
- 28. (Withdrawn) The method of claim 20 further comprising disposing a support platform above said cylindrical core assembly.
- 29. (Withdrawn) The method of claim 20 further comprising thermally coupling a heat sink below said cylindrical core assembly.
- 30. (Withdrawn) A method of making an apparatus for induction heating, said method comprising:

disposing a plurality of heat transfer plates radially with respect to a core axis;

disposing a plurality of core sections between respective pairs of said heat transfer plates, said core sections being shaped to form a cylindrical core assembly;

disposing a support platform above said cylindrical core assembly; and thermally coupling a heat sink below said cylindrical core assembly.

- 31. (Withdrawn) The method of claim 30 wherein said cylindrical core assembly has the shape of a circular cylinder.
- 32. (Withdrawn) The method of claim 30 further comprising disposing a cylindrical outer shell to surround said cylindrical core assembly.
- 33. (Withdrawn) The method of claim 30 wherein said heat transfer plates comprise a metal or combination of metals.

- 34. (Withdrawn) The method of claim 30 wherein said heat transfer plates comprise a material or combination of materials selected from the group consisting of aluminum nitride and boron nitride.
- 35. (Withdrawn) The method of claim 30 wherein said core sections comprise a ferromagnetic material.
- 36. (Withdrawn) The method of claim 30 further comprising disposing a coil winding above said cylindrical core assembly.
- 37. (Withdrawn) The method of claim 30 further comprising disposing an annular coil winding at least partially inside an annular recess in said cylindrical core assembly.